

Edge of Arlington Saw & Tool, Inc.

124 South Collins

Arlington, TX 76010

Phone: 817-461-7171 • Fax: 817-795-6651

Toll Free: 888-461-7171

Email: info@eoasaw.com

Website: www.eoasaw.com



Amana Tool Ripping Standard Saw Blades

Thank you for shopping with us! This blade is the classic ripper for both hardwood and softwood. It features the flat-top grind for cutting with the grain efficiently, ample gullets for fast chip-clearance, expansion slots, and turbulence-reducing copper plugs. Available in 18° and 20° hook configurations. The blade with the 20° hook angle features a thicker plate and cuts a wider kerf. Use in single and gang-rip saws. **Warning:** Before use, read saw blade safety guidelines in [Amana's catalog](#).

| Item # | Manufacturer | Diameter | Bore | Grind | Hook Angle | Kerf | Note | Pinholes | Plate | Teeth | Price |
|-----------|--------------|----------------|--------|-------|------------|---------|--|------------------|---------|-------|-----------------|
| 610240 | Amana Tool | 10 in (250 mm) | 5/8 in | FT | 20 deg | .142 in | -- | -- | .095 in | 24 | \$97.84 |
| 612300 | Amana Tool | 12 in (300 mm) | 1 in | FT | 20 deg | .160 in | -- | -- | .110 in | 30 | \$141.79 |
| 612300-30 | Amana Tool | 12 in (300 mm) | 30 mm | FT | 20 deg | .173 in | P.H. = pin-hole configuration. Example: 2/10/60 = 2 @ 10mm dia on 60mm circle. | 2/7/42 & 2/10/60 | .110 in | 30 | \$144.64 |
| 616360-30 | Amana Tool | 16 in (400 mm) | 30 mm | FT | 20 deg | .173 in | P.H. = pin-hole configuration. Example: 2/10/60 = 2 @ 10mm dia on 60mm circle. | 2/7/42 & 2/10/60 | .118 in | 36 | \$139.95 |
| 618320 | Amana Tool | 18 in (450 mm) | 1 in | FT | 20 deg | .157 in | -- | -- | .110 in | 32 | \$182.51 |

| | | | | | | | | | | | |
|-----------|------------|----------------|--------|----|--------|---------|--|------------------|---------|----|-----------------|
| 620360 | Amana Tool | 20 in (500 mm) | 1 in | FT | 20 deg | .173 in | -- | -- | .110 in | 36 | \$211.43 |
| 610200 | Amana Tool | 10 in (250 mm) | 5/8 in | FT | 18 deg | .126 in | -- | -- | .087 in | 20 | \$86.81 |
| 612240 | Amana Tool | 12 in (300 mm) | 1 in | FT | 18 deg | .126 in | -- | -- | .087 in | 24 | \$109.73 |
| 612240-30 | Amana Tool | 12 in (300 mm) | 30 mm | FT | 18 deg | .126 in | P.H. = pin-hole configuration. Example: 2/10/60 = 2 @ 10mm dia on 60mm circle. | 2/7/42 & 2/10/60 | .087 in | 24 | \$109.73 |
| 614280 | Amana Tool | 14 in (350 mm) | 1 in | FT | 18 deg | .137 in | -- | -- | .098 in | 28 | \$129.68 |
| 616320 | Amana Tool | 16 in (400 mm) | 1 in | FT | 18 deg | .137 in | -- | -- | .098 in | 32 | \$126.98 |
| 616320-30 | Amana Tool | 16 in (400 mm) | 30 mm | FT | 18 deg | .137 in | P.H. = pin-hole configuration. Example: 2/10/60 = 2 @ 10mm dia on 60mm circle. | 2/7/42 & 2/10/60 | .098 in | 32 | \$126.98 |
| 610240C | Amana Tool | 10 in (250 mm) | 5/8 in | FT | 20 deg | .142 in | Electro Blu Non-Stick Coating | -- | .095 in | 24 | \$111.04 |