

## Edge of Arlington Saw & Tool, Inc.

124 South Collins


Arlington, TX 76010

Phone: 817-461-7171 • Fax: 817-795-6651

Toll Free: 888-461-7171

Email: [info@eoasaw.com](mailto:info@eoasaw.com)

Website: [www.eoasaw.com](http://www.eoasaw.com)



### Amana Tool Solid Surface Modified Triple Chip Saw Blades

Thank you for shopping with us! This blade is designed for cutting plastic laminate, Plexiglas®, and solid surface materials such as Dupont Corian®, Wilsonart®, Gibraltar®, and Fountainhead®. The triple-chip grind is especially configured to leave a swirl-free cut in solid surface materials. Thick, stable plate reduces vibration that degrades the cut and shortens tool life. The blade is suitable for a variety of saw configurations. The 0° hook angle virtually eliminates self-feeding when used with a radial arm saw. *Note: P.H. denotes pin-hole configuration, if applicable. Example: 2/10/60 = 2 @ 10mm dia on 60mm circle.* **Warning:** Before use, read saw blade safety guidelines in [Amana's catalog](#).

Item #	Manufacturer	Diameter	Bore	Grind	Kerf	Pinholes	Plate	Teeth	Hook Angle	Price
610721	Amana Tool	10 in (250 mm)	5/8 in	MTC	0.126 in	--	.095 in	72	0 deg	<b>\$119.58</b>
610721C	Amana Tool	10 in (250 mm)	5/8 in	MTC	0.126 in	--	.095 in	72	0 deg	<b>\$123.30</b>
610721-30	Amana Tool	10 in (250 mm)	30 mm	MTC	0.126 in	2/7/42 & 2/10/60	.095 in	72	0 deg	<b>\$119.58</b>
612841	Amana Tool	12 in (300 mm)	1 in	MTC	0.126 in	--	.095 in	84	0 deg	<b>\$170.85</b>
612841-30	Amana Tool	12 in (300 mm)	30 mm	MTC	0.126 in	2/7/42 & 2/10/60	.095 in	84	0 deg	<b>\$170.85</b>
614961	Amana Tool	14 in (350 mm)	1 in	MTC	0.126 in	--	.102 in	96	0 deg	<b>\$170.85</b>
616109	Amana Tool	16 in (400 mm)	1 in	MTC	0.126 in	--	.102 in	108	0 deg	<b>\$317.25</b>