

Edge of Arlington Saw & Tool, Inc.

124 South Collins

Arlington, TX 76010

Phone:817-461-7171 • Fax: 817-795-6651

Toll Free: 888-461-7171

Email: info@eoasaw.com

Website: www.eoasaw.com



Everlast Special Purpose Cut-Off Saws - Alternate Top Bevel

Thank you for shopping with us!

Ideal for table saw use to provide fine finishing cuts in plywood, veneered panels, single-sided laminated panels, masonite (coated or uncoated), along with crosscutting in hard or soft woods. Use blades with more teeth when sawing thinner materials to provide quality cut and finish. All blades feature expansion slots with copper plugs to reduce noise, dissipate heat, and attenuate vibration during the cutting process.

Alternate Top Bevel - ATB - Each tooth has top bevel typically between 10 and 20 degrees. Two teeth are required to provide a full kerf cut. Provides low cutting pressures, which reduce material tearing during the cutting process and provides a fine cutting finish. Best performance cross cutting.



Item #	Manufacturer	Bore	Diameter	Grind	Kerf	Note	Pinholes	Plate	Teeth	Price
SPE1080A	Everlast	5/8 in	10 in	ATB	0.125 in (3.2 mm)		0.087 in2.2 mm	0.087 in - 2.2 mm	80	\$138.46
SPE1280A	Everlast	1 in	12 in	ATB	0.135 in (3.4 mm)		0.095 in2.4 mm	0.095 in - 2.4 mm	80	\$170.79
SPE1210A	Everlast	1 in	12 in	ATB	0.135 in (3.4 mm)		0.095 in2.4 mm	0.095 in - 2.4 mm	100	\$192.44
SPE1480A	Everlast	1 in	14 in	ATB	0.150 in (3.8 mm)		0.109 in2.8 mm	0.109 in - 2.8 mm	80	\$199.84
SPE1410A	Everlast	1 in	14 in	ATB	0.150 in (3.8 mm)		0.109 in2.8 mm	0.109 in - 2.8 mm	100	\$227.07
SPE1680A	Everlast	1 in	16 in	ATB	0.150 in (3.8 mm)		0.109 in2.8 mm	0.109 in - 2.8 mm	80	\$236.62

SPE1610A	Everlast	1 in	16 in	ATB	0.160 in (4.1 mm)		0.118 in3.0 mm	0.118 in - 3.0 mm	100	\$287.20
SPE1620A	Everlast	1 in	16 in	ATB	0.160 in (4.1 mm)		0.118 in3.0 mm	0.118 in - 3.0 mm	120	\$308.22
SPE1880A	Everlast	1 in	18 in	ATB	0.175 in (4.4 mm)		0.134 in3.4 mm	0.134 in - 3.4 mm	80	\$241.67
SPE1810A	Everlast	1 in	18 in	ATB	0.175 in (4.4 mm)		0.134 in3.4 mm	0.134 in - 3.4 mm	100	\$331.91
SPE1820A	Everlast	1 in	18 in	ATB	0.175 in (4.4 mm)		0.134 in3.4 mm	0.134 in - 3.4 mm	120	\$357.65
SPE30072A5	Everlast	30 mm	300 mm	ATB	0.125 in (3.2 mm)	MICRO-5 extra hard tips provide 3-5 times longer service than standard carbide.	2/7/42; 2/10/60	0.087 in - 2.2 mm	72	\$168.65
SPE2080A	Everlast	1 in	20 in	ATB	0.175 in (4.4 mm)		0.134 in3.4 mm	0.134 in - 3.4 mm	80	\$372.22
SPE2010A	Everlast	1 in	20 in	ATB	0.175 in (4.4 mm)		0.134 in3.4 mm	0.134 in - 3.4 mm	100	\$380.18
SPE2020A	Everlast	1 in	20 in	ATB	0.175 in (4.4 mm)		0.134 in3.4 mm	0.134 in - 3.4 mm	120	\$433.05
SPE2280A	Everlast	1 in	22 in	ATB	0.190 in (4.8 mm)		0.148 in3.8 mm	0.148 in - 3.8 mm	80	\$555.15
SPE2210A	Everlast	1 in	22 in	ATB	0.190 in (4.8 mm)		0.148 in3.8 mm	0.148 in - 3.8 mm	100	\$518.40
SPE2220A	Everlast	1 in	22 in	ATB	0.190 in (4.8 mm)		0.148 in3.8 mm	0.148 in - 3.8 mm	120	\$592.80
SPE2480A	Everlast	1 in	24 in	ATB	0.190 in (4.8 mm)		0.148 in3.8 mm	0.148 in - 3.8 mm	80	\$521.07
SPE2410A	Everlast	1 in	24 in	ATB	0.190 in (4.8 mm)		0.148 in3.8 mm	0.148 in - 3.8 mm	100	\$692.00
SPE25080A5	Everlast	30 mm	250 mm	ATB	0.125 in (3.2 mm)	MICRO-5 extra hard tips provide 3-5 times longer service than standard carbide.	2/7/42	0.087 in (2.2 mm)	80	\$154.79