

Edge of Arlington Saw & Tool, Inc.

124 South Collins
 Arlington, TX 76010
 Phone:817-461-7171 • Fax: 817-795-6651
 Toll Free: 888-461-7171
 Email: info@eoasaw.com
 Website: www.eoasaw.com

HMD905 SPECIFICATIONS	
Electrical System	115V, 50/60 Hz - 10A, 1150W 230V, 50/60 Hz - 5A, 1150W
Motor	9A (115V), 4.5A (230V), 250/450 RPM
Diameter	7/16"- 1-5/8" (12mm - 41mm)
Depth	2" (50mm)
Cutter/Mount	"12,000-Series" & Copperhead™ & Fusion™ cutters, 3/4" shank
Dimensions	22-13/16" H x 7-11/16" W x 11-3/4" L (579mm H x 195mm W x 299mm L)
Swivel Area	1-1/8" W x 1-3/8" L (28.5mm H x 34.9mm W)
Base	3-1/8" W x 6-9/16" L (79mm W x 167mm L)
Magnet	1" Plate(25mm) Dead Lift 1790 lb. (794 kg) Drillpoint Breakaway 995 lb. (433 kg) 3/8" Plate(9.5mm) 1310 lb. (594 kg) 710 lb. (322 kg)
Magnet (Swivel)	1" Plate(25mm) Dead Lift 1340 lb. (608 kg) Drillpoint Breakaway For: 695 lb. (315 kg) Back: 835 lb. (379 kg) 3/8" Plate(9.5mm) 1015 lb. (460 kg) For: 503 lb. (228 kg) Back: 695 lb. (315 kg)
Weight	35 lb. (15.9 kg) • Shipping 52 lb. (23.6 kg)
Weight (Swivel)	38 lb. (17.2 kg) • Shipping 55 lb. (24.9 kg)

Item #0905109, Hougen Portable Magnetic Drills HMD905 **\$2,400.00**

NOT ELIGIBLE FOR FREE FREIGHT—Call 817-461-7171 for Freight Charges

For more information on this drill, including specifications sheet, please see images to the left.

Powerful workhorse with a large capacity and built in versatility

- Powerful high torque Hougen motor and gears
- Two speed gear box - 250 & 450 RPM
- Pilot light for low light conditions and greater hole accuracy
- Two stage magnet. Engages full power when motor is on
- Available with or without the swivel base
- Positive slug ejection
- Many accessories are available
- Feed handles quickly change from side to side
- Lift detector safety system
- Integrated gravity fed coolant bottle
- Carrying case included
- One year warranty

Swivel base adds even greater versatility

- Precisely line up your pilot with the hole's center location
- One stroke lock and unlock handle
- Great for horizontal, overhead, tight areas, and getting out over another piece of steel

*All drills include: carrying case, pint of coolant, safety chain, hex wrenches, but do not include an on/off switch for the pilot light.

**Fabricator's kit includes drill, 1/2" drill chuck, adapter, and " 12,000 Series" cutter kit.

SPECIFICATIONS

Part Descp.	Fabricator's Kit/Fractional
Cut Depth	2 in
Dimensions	22 13/16 in H x 7 11/16 in W x 11 3/4 in L (579mm x 195mm x 299mm)
Includes	Carrying case, coolant bottle, drill chucks, twist drill adapter, tapping kit, countersink kit, ratchet drive, portable vac pad, cutter fluid, lube
Type	115V (Voltage)
Note	*NOT ELIGIBLE FOR FREE FREIGHT Call 817-461-7171 for Freight Charges*
Manufacturer	Hougen