

Edge of Arlington Saw & Tool, Inc.

124 South Collins
Arlington, TX 76010
Phone: 817-461-7171 • Fax: 817-795-6651
Toll Free: 888-461-7171
Email: info@eoasaw.com
Website: www.eoasaw.com



Item #33125, Techniks PowerCOAT ER25 High-Speed 35mm Mini Nut - Torque 26 ft/lbs \$82.00

Thank you for shopping with us! Use ER High-Speed mini nuts for applications where speed exceeds 10,000 RPMs. They are balanced to G2.5 for 20,000 RPMs. For collet holders and multi-spindle heads where center or shoulder distances are important. -For minimum nose O.D. applications -Increases holding power by 75% -High speed nuts balanced to 20,000 RPM PowerCOAT Nuts outperform bearing nuts! -Rubber bearing seals on bearing nuts eventually fail, and then dust contaminates bearings to make them freeze up. -Uncoated threads limit holding power. -Bearing nuts cannot be balanced because they have moving parts so cutting tools wear prematurely. CNC Routers run better with PowerCOAT! PowerCOAT nuts greatly reduce friction between the nut, collet shoulder, and tool holder threads to increase down-force on the collet, collapsing tighter around the tool shank. This improves holding power and runout (T.I.R.). Better T.I.R. means cutting is faster and smoother, and tool life is also improved.



SPECIFICATIONS	
Manufacturer	Techniks
Diameter	35mm
Recommended Torque	26 ft/lbs
Style	ER25 high speed mini nut
Thread Size/Length	M30x1.0
Wrench	0.4624
Height	21mm