

Edge of Arlington Saw & Tool, Inc.

124 South Collins
Arlington, TX 76010
Phone: 817-461-7171 • Fax: 817-795-6651
Toll Free: 888-461-7171
Email: info@eoasaw.com
Website: www.eoasaw.com



313009 Carbide Tipped
Through-Hole Boring Bit R/H
3/8 Dia x 57mm Long x 10mm
Shank



413009 Carbide Tipped
Through-Hole Boring Bit L/H
3/8 Dia x 58mm Long x 10mm
Shank

Item #413009, Amana Tool Through-Hole with V-Point Carbide-Tipped 57MM Long

Thank you for shopping with us!

Industrial Through-Hole with V-Point Boring Bits are coated with a non-stick coating for longer lasting cutting edge and tool life.

Amana Tool® dowel drills are coated with a special Polytetrafluoroethylene (PTFE), a non-stick color coating. In cases where the carbide tip cutting edges are coated, there is no need to sand the coating off before use. Once the tool starts drilling, the coating is cleared off the needed cutting edge right away. Amana's coating is applied onto the bit at a temperature of 570° F. The coating reduces the friction between the chip and the body inside the flute and it helps to clear the chips out of the hole during the drilling to create a cooler drilling area, no burning, and longer lasting cutting edge.

Not to be used in portable drills or handheld routers. Max RPM = 8,000

SPECIFICATIONS

Manufacturer	Amana Tool
Cut Height, Length, or Width	35 mm
Overall Length	57 mm
Shank	10 mm