## Edge of Arlington Saw & Tool, Inc.

124 South Collins Arlington, TX 76010

Phone:817-461-7171 • Fax: 817-795-6651

Toll Free: 888-461-7171
Email: info@eoasaw.com
Website: www.eoasaw.com



## Item #45793, Amana Tool CNC Double-Edge Folding V & Rectangular Groove for Shaping Aluminum Composite Material Carbide-Tipped Router Bits \$68.29

Thank you for shopping with us!

These bits are widely used as cladding for many diverse applications such as office buildings, hospitals, convention centers, airports, hotels. Routing V-shaped & Rectangular grooves, whereby the aluminum cover and a part of the polyethylene core is removed, allows folding/creasing the remaining material by hand. Designed for cutting and scoring aluminum sandwich materials including:

- Aluminum, Clay, Zinc & Wood Composite Panels
- Aluminum Composite Materials (ACM)
- Aluminum Composite Panel (ACP)\*
- Aluminum 5052
- ALPOLIC® Copper Composite Material (CCM)
- Alucobond®
- Alupanel®
- Dibond®
- Durabond\*\*
- e-panel<sup>™</sup>
- Etalbond®
- Phenolics
- Plastic/Acrylic
- Plexiglas®
- Titanium Composite Material (TCM)
- Wood

\*Aluminum Composite Panel (ACP) is a type of ACM flat panel that consists of two thin aluminum sheets bonded to a non-aluminum core. ACPs are frequently used for external cladding or facades of buildings, insulation, and signage. \*\*Durabond is a polyethylene core with 0.3mm colored aluminum sheet on either side, prefinished requiring no decoration. Thank you for shopping with us!

SPECIFICATIONS	
Diameter	3/4 in
Cut Height, Length, or Width	5/16 in
Diameter (D1)	0.118 in
Length	

SPECIFICATIONS		
Manufacturer	Amana Tool	
Note		
Overall Length	2 1/8 in	
Shank	1/2 in	
Туре	V	
Angle	90 deg / 45 deg (a1)	