

Edge of Arlington Saw & Tool, Inc.

124 South Collins
Arlington, TX 76010
Phone:817-461-7171 • Fax: 817-795-6651
Toll Free: 888-461-7171
Email: info@eoasaw.com
Website: www.eoasaw.com



Item #46132, Techniks PowerCOAT Ultra High-Speed 50mm ER32 Nut - Torque 100 ft/lbs \$67.00

Thank you for shopping with us! PowerCOAT nuts greatly reduce friction between the nut, collet shoulder, and tool holder threads to increase down-force on the collet, collapsing tighter around the tool shank. This improves holding power and runout (T.I.R.). Better T.I.R. means cutting is faster and smoother, and tool life is also improved. -40% more holding power than bearing nuts. - Better rigidity and T.I.R. (runout). -Balanced to 25,000 RPM PowerCOAT Nuts outperform bearing nuts! -Rubber bearing seals on bearing nuts eventually fail, and then dust contaminates bearings to make them freeze up. -Uncoated threads limit holding power. -Bearing nuts cannot be balanced because they have moving parts so cutting tools wear prematurely. CNC Routers run better with PowerCOAT!

SPECIFICATIONS	
Manufacturer	Techniks
Diameter	50mm
Note	Max Speed 50,000
Recommended Torque	100 ft/lbs
Style	ER32 high speed slot nut
Thread Size/Length	M40x1.5
Wrench	4616
Height	23mm