

Edge of Arlington Saw & Tool, Inc.

124 South Collins
 Arlington, TX 76010
 Phone:817-461-7171 • Fax: 817-795-6651
 Toll Free: 888-461-7171
 Email: info@eoasaw.com
 Website: www.eoasaw.com





Item #46268, Amana Tool Solid Carbide CNC Spiral Carbon Graphite & Carbon Fiber Panel Cutting 1/2 x 2 1/8 x 1/2 Shank Downcut Router Bit \$102.68

Thank you for shopping with us!

Designed to produce a minimum failure in composite materials such as layers separating and significant loss of mechanical toughness. The rapidly growing use of Carbon Fiber Reinforced Polymers (CFRP) necessitates tooling designed to effectively meet the challenges of such composites. Experts have recognized the need for tool geometry combining a highly abrasion-resistant carbide substrate, generous fluting, and an impact zone that not only “shatters” the hard carbon fibers but also keeps heat down. These industrial router bits combat abrasion, heat, and the breakdown of composites for clean, accurate cuts.

Excellent for cutting: +Carbon Fiber +Carbon Fiber Reinforced Polymer (CFRP) +Carbon Graphite +Composite Materials +Fiberglass +Fiberglass PCB Board +Fiber Reinforced Plastic (FRP) +Glass Fiber Reinforced Polymer - Plastic Materials (GFR) +Glass Reinforced Plastic (GRP) +G10 = High-pressure fiberglass laminate, a kind of composite material +G10 / FR-4 Glass Epoxy Composite Laminate Material +G11 / FR-5 Glass Epoxy Composite Laminate Material +Micarta® (Brand name for composites of linen, canvas, paper, fiberglass, carbon fiber or other fabric in a thermosetting plastic.) +Phenolic +Phenolic " Garolite" G-7 +Plastic PVC & Acrylic +Thermoset Composites +Thermosetting Plastics



SPECIFICATIONS	
Manufacturer	Amana Tool
Cut Height, Length, or Width	2 1/8 in
Diameter	1/2 in
Flute Geometry	Downcut
Flute	1

SPECIFICATIONS

Overall Length

4 in

Shank

1/2 in