


Edge of Arlington Saw & Tool, Inc.

124 South Collins
Arlington, TX 76010
Phone: 817-461-7171 • Fax: 817-795-6651
Toll Free: 888-461-7171
Email: info@eoasaw.com
Website: www.eoasaw.com



Item #46416-K, Amana Tool Solid Carbide Spektra™ Extreme Tool Life Coated Spiral Plunge 1/4 Dia x 1-1/8 x 1/4 Inch Shank Downcut \$53.44

Thank you for shopping with us! Spiral-flute bits combine a shearing action in cutting with an augering action in chip clearance. The shearing action yields an especially clean accurate cut while the augering action clears chips from the cut. The 'Up-Cut' shears from the bottom up pulling chips from the bottom up thus allowing deeper penetration with less stress on the tool. An excellent choice for mortising. Special unique carbide grade increased clearance geometry and razor-sharp cutting edges with polished flutes provide a superior finish and longer tool life especially in abrasive materials. Great for production settings and excellent for creating grooves and dado cuts in particleboard plywood and laminate. Primarily used on CNC machines and other automatic routers. Can be used with handheld and table-mounted portable routers. Excellent for cutting: Laminate, Melamine, Melamine Particle Board, MDF, Veneered Plywood, Wood Our Spektra™ bits feature a nACo® nanocomposite coating with an extreme nanohardness and heat resistance. With a brilliant distinctively-tinted coloring, nACo® provides additional improvements in four critical aspects of router tooling: -nACo® coating is a micro-thin ceramic coating that enables the tool's cutting edge to retain crucial sharpness and lubricity. This provides longevity and produces cutting results of the highest quality. -Coating prevents high heat and oxidation, which is detrimental to cutting tool performance. -Multi-colored hues, while attractive, will dissipate upon use and yet coating will remain fully effective. -nACo® offers approximately 4,500 Vickers for impressive solid hardness on cutting areas of the tool, for an increase up to 2.5 times compared to uncoated bits. Note: Blue based color dissipates immediately upon use. nACo® nanocomposite coating will not wear off.



SPECIFICATIONS

| | |
|-------------------------------------|------------|
| Manufacturer | Amana Tool |
| Diameter | 1/4 in |
| Cut Height, Length, or Width | 1 1/8 in |
| Flute Geometry | Downcut |
| Flute | 2 |
| Overall Length | 3 in |
| Shank | 1/4 in |
| Note | |