

Edge of Arlington Saw & Tool, Inc.

124 South Collins
Arlington, TX 76010
Phone: 817-461-7171 • Fax: 817-795-6651
Toll Free: 888-461-7171
Email: info@eoasaw.com
Website: www.eoasaw.com



Item #48058-D, Amana Tool High Performance Solid Carbide Fiberglass and Composite Cutting 1/2 x 1 1/8 x 1/2 Shank AlTiN Coated Drill End Router Bit \$109.20

Thank you for shopping with us!

Amana Tool offers an array of unique extended life Aluminum Titanium Nitride (AlTiN) coated router bits for all your fiberglass application needs. Premium AlTiN coating provides double the hardness of cutting edges resulting in quantum increases in productivity, either in terms of speed or longevity, with or without coolant. Coating helps prevent edge failures due from vibration and shock during CNC and manual feed applications. For plunging cleaner slots with minimum workpiece deflection.

Excellent for Cutting:

- Carbon Fiber
- Edging and Slotting All Carbon Fiber Reinforced Polymer - Plastic Materials (CFRP)
- Composite Materials
- Fiberglass
- Fiberglass PCB Board
- Fiber Reinforced Plastic (FRP)
- Glass Reinforced Plastic (GRP)
- G-10 / FR-4 and G11 / FR-5 Glass Epoxy Composite Laminate Material
- Micarta® (Brand name for composites of linen, canvas, paper, fiberglass, carbon fiber or other fabric in a thermosetting plastic.)
- Phenolic
- Thermoset Composites
- Thermosetting Plastics

AlTiN coating has many benefits:

- Extra wear resistance
- Allows for faster feed and speed rates
- Cutting edge protected from wear
- Better chip evacuation
- Less heat buildup
- Superior cutting quality and extended tool life



SPECIFICATIONS

Manufacturer	Amana Tool
Diameter	1/2 in
Cut Height, Length, or Width	1 1/8 in
Note	--
Overall Length	3 in
Shank	1/2 in