

## Edge of Arlington Saw & Tool, Inc.

124 South Collins  
Arlington, TX 76010  
Phone: 817-461-7171 • Fax: 817-795-6651  
Toll Free: 888-461-7171  
Email: [info@eoasaw.com](mailto:info@eoasaw.com)  
Website: [www.eoasaw.com](http://www.eoasaw.com)



### Item #508400, Amana Tool Carbide-Tipped Adjustable ACM Scoring Set 8 Inch Dia x 2x20T, 18 Deg, 5/8 Bore (Industrial) \$197.10

Thank you for shopping with us!

Carbide-Tipped - V-Groove with 2.0 (0.080") - 3.0mm (0.118") V-Flat Bottom.



Shim set #055-108 & instruction booklet included.



Designed for scoring Aluminum

Composite (sandwich) Materials with 60°, 90°, 108°, and 135° angle V-grooves with flat bottom. Set contains two saw blades and a shim set. Add the shims between the blades to achieve your desired flat bottom cut width. Widely used for cladding many diverse exterior and interior applications. The long lasting durability of the material makes it an excellent choice for buildings, signage, displays, etc.

Excellent for scoring: Aluminum, Clay, Zinc & Wood Composite Panels; Aluminum Composite Materials (ACM); Aluminum Composite Panel (ACP)\*; ALPOLIC® Copper Composite Material (CCM); Alucobond®; Alupanel®; Dibond®; Durabond\*\*; e-panel™; Etalbond®; Titanium Composite Material (TCM); Trespa®.

The materials are used on facades and interior wall surfaces that can be found in office buildings, hospitals, convention centers, airports, and hotels, along with exterior signage.


\*ACP is a type of ACM flat panel that consists of two thin aluminum sheets bonded to a non-aluminum core. ACPs are frequently used for external cladding or facades of buildings, insulation, and signage.

\*\*Durabond is a polyethylene core with 0.3mm colored aluminum sheet on either side, pre-finished requiring no decoration.

**Warning:** This set requires a custom zero clearance throat plate.

**Warning:** Not to be used with portable saws.

**Warning:** Before use, read saw blade safety guidelines in [Amana's catalog](#).



## SPECIFICATIONS

<b>Manufacturer</b>	Amana Tool
<b>B1</b>	0.161 in
<b>Diameter</b>	8 in
<b>Bore</b>	5/8 in
<b>Grind</b>	ACM
<b>Hook Angle</b>	18 deg
<b>Kerf</b>	Range: 10.2-11.2mm; (0.078-0.118 in Flat Bottom Range)
<b>Note</b>	Warning: This set requires a custom zero clearance throat plate. Warning: Not to be used with portable saws. Shim set #DSS-108 & instruction booklet included.
<b>Teeth</b>	2x20
<b>Angle</b>	45 °