

## Edge of Arlington Saw & Tool, Inc.

124 South Collins  
Arlington, TX 76010  
Phone: 817-461-7171 • Fax: 817-795-6651  
Toll Free: 888-461-7171  
Email: [info@eoasaw.com](mailto:info@eoasaw.com)  
Website: [www.eoasaw.com](http://www.eoasaw.com)



### Item #77-510, Freud Premier Solid Carbide Mortise Compression Spiral Bit **\$90.01**

Thank you for shopping with us!

**Application:** Mortises or grooves with a perfect top surface, or through-cuts in thin double-sided veneers and laminates

- Shorter up shear length allows bit to be used for grooves and mortises without chipping top surface.
- Also ideal for through-cuts in double-sided sheets that are 5/8" thick or less.
- Combination of up and down shear flutes eliminates chipping on both sides of double-sided panels.
- Routs melamine, veneer plywood, and other double-sided materials, as well as hardwood and softwood.
- Use on CNC and other automatic routers as well as handheld and table-mounted portable routers.
- Double flute spirals are for extra clean cuts at faster feed rates.
- Black I.C.E.™ coating for cool cutting edge and superior chip evacuation. Black I.C.E.™ + Freud TiCo™ Hi-Density Carbide = 2X increased life and performance vs. standard uncoated bits. Black ICE Router Bits—the slickest technology in solid carbide router bits—protects solid carbide cutting edge by creating a slick, lubricant-like action for a cool cutting edge and superior chip evacuation.

77-510



## SPECIFICATIONS

**Manufacturer**

Freud Tools

## SPECIFICATIONS

<b>Diameter</b>	1/2 in
<b>Cut Height, Length, or Width</b>	1 3/8 in
<b>Flute</b>	Two Flute
<b>Overall Length</b>	3 1/2 in
<b>Shank</b>	1/2 in
<b>Upcut Length</b>	5/16 in