

Edge of Arlington Saw & Tool, Inc.

124 South Collins
Arlington, TX 76010
Phone:817-461-7171 • Fax: 817-795-6651
Toll Free: 888-461-7171
Email: info@eoasaw.com
Website: www.eoasaw.com



Item #806-004, Mastercut 2 Flute O Flute Upcut Slow Spiral (Soft & Hard Plastics) \$24.91

Thank you for shopping with us!

Material Finish-Top: Poor
Material Finish-Bottom: Excellent

Spiral flute router bits should only be used in automatic feed operations. They're good for use on all materials.

Upcut routers are used when a good bottom finish is desired on the material. Chips flow in an upward direction.

2 flute routers work well with harder materials, providing an excellent finish to the material.

Endmill Points are most often found on 3 and 4 flute routers. They are good for achieving a smooth finish on a flat bottom surface, and are commonly used in the plastic routing industry.

SPECIFICATIONS

| | |
|-------------------------------------|-------------|
| Diameter | 1/4 in |
| Cut Height, Length, or Width | 3/4 in |
| End Pt Type | Endmill |
| Flute Geometry | Upcut |
| Flute | 2 'O' Flute |
| Helix Angle | 11 deg |
| Overall Length | 2 1/2 in |
| Shank | 1/4 in |
| Manufacturer | Mastercut |