

## Edge of Arlington Saw & Tool, Inc.

124 South Collins  
Arlington, TX 76010  
Phone: 817-461-7171 • Fax: 817-795-6651  
Toll Free: 888-461-7171  
Email: [info@eoasaw.com](mailto:info@eoasaw.com)  
Website: [www.eoasaw.com](http://www.eoasaw.com)



### **Item #AMS-147, Amana Tool 3-Pc. Carbide-Tipped V-Groove 90°, 108°, 135° Angles for Double Edge Folding Aluminum Composite Material (ACM) Panels 1/2" Shank Router Bit Set \$171.67**

Thank you for shopping with us! Designed for shaping Aluminum Composite (sandwich) Materials (ACM) with flat bottom V-grooves. Routing V-shaped grooves, whereby the aluminum cover and a part of the polyethylene core is removed, allows folding/creasing the remaining material by hand. Ideal for wall panel fabrication. ACM is widely used for cladding many diverse exterior and interior applications such as office buildings, hospitals, convention centers, airports, and hotels. The long lasting durability of the material makes it an excellent choice for buildings, signage, displays, etc. Designed for cutting and scoring aluminum sandwich materials including: Acetate Aluminum, Brass, Bronze, Clay, Zinc & Wood Composite Panels, Aluminum 5052 Aluminum Composite Materials (ACM), Aluminum Composite Panel (ACP)\*, ALPOLIC® Copper Composite Material (CCM), Alucobond®, Alupanel®, Bakelite, Dibond®, Durabond\*\*, e-panel™, Etalbond®, Nylon, PE and FR Cores, Phenolics, Plastic/Acrylic, Plexiglas®, PVC, Thermoplastics, Titanium Composite Material (TCM), Wood. \*Aluminum Composite Panel (ACP) is a type of ACM flat panel that consists of two thin aluminum sheets bonded to a non-aluminum core. ACPs are frequently used for external cladding or facades of buildings, insulation, and signage. \*\*Durabond is a polyethylene core with 0.3mm colored aluminum sheet on either side, pre-finished requiring no decoration. Bits can be purchased separately.

#### SPECIFICATIONS

<b>Manufacturer</b>	Amana Tool
<b>Includes</b>	45794, 45797, 45791
<b>No. of Pieces</b>	3