Edge of Arlington Saw & Tool, Inc.

124 South Collins Arlington, TX 76010 Phone:817-461-7171 • Fax: 817-795-6651 Toll Free: 888-461-7171 Email: info@eoasaw.com Website: www.eoasaw.com



D1296N

Item #D1296N, Diablo 12" X 96 Tooth Medium Aluminum Saw Blade \$74.18

Thank you for shopping with us!

Diablo's next generation Aluminum saw blades are optimized for cutting thin (up to 1/8"), medium (3/32"-1/4"), and thick (3/16"-7/16") aluminum metals. Featuring the new, specially formulated Diablo TiCo[™] Super-Density Micro-Grain Carbide, these radical blades withstand impact, reduce wear, provide clog free cuts, and last longer than standard carbide in metal cutting applications. The specially formulated metal cutting carbide teeth feature a Triple Chip Grind (TCG) Tooth Design for clean, burr-free finishes, virtually eliminating any type of rework. Tri-Metal Shock Resistant Brazing allows these Aluminum blades to slice through metal materials while withstanding extreme impact for maximum durability. Diablo's Aluminum saw blade series is ideal for corded and cordless saws when on-the-job cutting non-ferrous metals such as aluminum extrusions, copper pipe, brass plate, etc.

 $\mathsf{Tico}^{\,\mathrm{m}}$ Super-Density Micro-Grain Carbide for extreme cutting life and clog free cuts

Tri-Metal Shock Resistant Brazing for extreme impact and maximum durability

Triple Chip Grind (TCG) Tooth Geometry for maximum life, speed, and durability, giving clean, burr-free cuts

Laser-Cut Stabilizer Vents for trapping noise and reducing vibration for accuracy and durability

Perma-SHIELD® Non-Stick Coating for protection against heat, gumming, and corrosion

Ideal For: Cutting aluminum, copper, plastics, brass, and fiberglass

Suggested Projects: Remodeling/Demolition, Electrical & Plumbing

SPECIFICATIONS	
Manufacturer	Diablo Tools
Arbor	1 in
Diameter	12 in
Teeth	96 TCG
Hook Angle	-5 deg

SPECIFICATIONS	
Kerf	0.091 in
Plate	0.071 in
Application	Cutting aluminum, copper, plastics, brass, and fiberglass
Unit Price	
Pack Quantity	1