



Edge of Arlington Saw & Tool, Inc.

124 South Collins
 Arlington, TX 76010
 Phone: 817-461-7171 • Fax: 817-795-6651
 Toll Free: 888-461-7171
 Email: info@eoasaw.com
 Website: www.eoasaw.com



TOOLS



Item #LU87R012, Freud Thin Kerf Rip Blades: Series LU87R (Copy) \$65.77

Thank you for shopping with us!

Application: Heavy-Duty Ripping Blades for Underpowered Saws

This blade gives new life to underpowered table saws and radial arm saws because the thin kerf does not require much horsepower. The Perma-SHIELD® coating helps this blade pull 1/3 less on the saw, which translates to over 33% more cutting power. The ideal working range is from 3/4" to 2 3/4" thick.

CUTS



Hardwoods

Softwoods

Laminate

Plywood

OSB

Premium TiCo™ HI-Density Carbide Ripping Blend for Maximum Performance. Thin Kerf allows for faster feed rate and reduced waste. Positive Hook Angles for fast cutting and easy feeding in ripping applications.

Perma-Shield™ Non-Stick Coating reduces blade drag, protects the blade from corrosion and pitch build-up.

Ideal For: Heavy-Duty Ripping Blades For Underpowered Saws. Depth of cut (3/4" to 2-3/4").

TIP: Maintain a proper feed rate. Feeding too slow causes burning of the material. Feeding too fast can be dangerous and produces a poor dull cut.

SPECIFICATIONS

Kerf	0.099
Diameter	12 in
Arbor	5/8 in
Bevel	15 deg
Plate	.071 in
Teeth	30 ATB
Type	Perma-SHIELD
Manufacturer	Freud Tools