Edge of Arlington Saw & Tool, Inc.

124 South Collins Arlington, TX 76010

Phone:817-461-7171 • Fax: 817-795-6651

Toll Free: 888-461-7171 Email: <u>info@eoasaw.com</u> Website: www.eoasaw.com






Item #HG220T420, Amana Tool Carbide-Tipped Hollow Ground 220mm Dia x 42T HG, -6 Deg, 30mm Bore

Thank you for shopping with us!

The specially designed saw blade makes exceptionally smooth cuts in melamine and other coated boards, without the need for scoring. The unique hollow grind, which pairs a triple-chip tooth with a raker tooth that's ground to a concave profile, produces crisp clean cuts. The grind is commonly used in vertical panel saws, such as those made by Striebig® and Holz-Her®. The negative hook angle is particularly suitable for vertical panel saws.

Note: P.H. denotes pin-hole configuration, if applicable. Example: 2/10/60 = 2 @ 10mm dia on 60mm circle.

Warning: Before use, read saw blade safety guidelines in Amana's catalog.



Melamine Single & Double Sided

SPECIFICATIONS	
Manufacturer	Amana Tool
Diameter	220mm
Bore	30mm
Grind	Hollow Ground (HG)
Kerf	0.126 in
Machine	Holz-Her
Pinholes	2/7/42

SPECIFICATIONS	
Plate	0.126 in
Teeth	42
Hook Angle	6 deg negative hook