

## Edge of Arlington Saw & Tool, Inc.

124 South Collins  
Arlington, TX 76010  
Phone:817-461-7171 • Fax: 817-795-6651  
Toll Free: 888-461-7171  
Email: [info@eoasaw.com](mailto:info@eoasaw.com)  
Website: [www.eoasaw.com](http://www.eoasaw.com)



### Item #HM-35566DX, Tenryu Heavy Metal Series \$122.40

Thank you for shopping with us!

Circular Saws. Low RPM Dry Cut Saws.

These blades ROCK! Take your pick! both the Heavy Metal and the Heavy Metal Plus are designed for users seeking affordability, quick cutting, and long life, especially in heavier mild steel profiles and plate.

Common end-users are:

- Industrial staircases, railings, mezzanines, platforms, grating, trailers, strut, etc.
- Rigging, oil field services equipment
- Plant and equipment maintenance and repair (MRO)

Thin kerf design coupled with lower tooth count for effortless cutting of thick-wall mild steel (7" and 7 1/4" blades: 1/8" -1/4" , 8" and 9" blades: 1/8" -1/2" , and 14" blades: 1/8" -1/2" ).

Good for metal cutting saws (Evolution, SteelMax, MK Morse, Milwaukee, Jepson, Makita, DeWalt, Worm-Drive circular saws, and others).

The Heavy Metal Series features select C-6 grade micro-grain carbide and affords excellent value and long cut life. The Heavy Metal Series incorporates an industry-leading super thin kerf design, triple-chip grind (TCG) and modified triple-chip grind (MTCG) tooth geometries, and is well suited for job site and shop applications.

Note: Please note all safety instructions before use and adhere to instructions for maximum RPM speeds. Always wear eye protection that meets ANSI Z87.1 requirements and properly functioning upper and lower guards.

## SPECIFICATIONS

<b>Manufacturer</b>	Tenryu
<b>Application</b>	1/8 in - 1/2 in wall thickness
<b>Arbor</b>	1 in
<b>Diameter</b>	14 in
<b>Grind</b>	MTCG
<b>Kerf</b>	0.087

## SPECIFICATIONS

<b>Rake</b>	2
<b>RPM</b>	1,800
<b>Teeth</b>	66