


## Edge of Arlington Saw & Tool, Inc.

124 South Collins  
Arlington, TX 76010  
Phone:817-461-7171 • Fax: 817-795-6651  
Toll Free: 888-461-7171  
Email: [info@eoasaw.com](mailto:info@eoasaw.com)  
Website: [www.eoasaw.com](http://www.eoasaw.com)



### Item #LB16121, Amana Tool Carbide-Tipped Non-Melt Plastic 16 Inch Dia x 120T M-TCG, -2 Deg, 1" Bore \$373.20

Thank you for shopping with us!

When cutting acrylics and plastics, "chip-welding" —a melting of the material—is a concern. But not with these Non-Melt blades. With a modified triple-chip grind and a 2° negative hook angle, they produce less heat than a standard blade, leaving a crisp and smooth edge in acrylic sheets, corrugated polypropylene, HDPE, Lexan®, Plexiglas®, polycarbonates, Teflon®, Coroplast®, and other plastics.

**Warning:** Before use, read saw blade safety guidelines in [Amana's catalog](#).

Excellent for Cutting: -Plastics -Acrylonitrile Butadiene Styrene (ABS) - Acetal -Acrylic -Acrylic Sheets -Alupanel® -Copolymer -Coroplast®\* - Correx Boards -Corrugated Polypropylene -Delrin -Ethylene-Vinyl Acetate - Foam Board -Gatorfoam®\*\* -High Density Polyethylene (HDPE) -High Impact Polystyrene (HIPS) -Low Density Polyethylene (LDPE) -Lucite® - Mechanical/Engineered Plastics -Nitrile Rubber -Nylon -Perspex® Cast Acrylic Sheet -Plastic Laminate Flooring -Plexiglas® -Poly (methyl methacrylate) (PMMA) -Polycarbonate (Lexan™) -Polyethylene (PE) - Polyethylene Terephthalate (PET) -Polyethylene Terephthalate Glycol-Modified (PETG / PET-G) -Polypropylene (PP) -Solid Surface -Styrene-Acrylonitrile -Styrene-Butadiene Rubber (SBR) -Styrene-Isoprene-Styrene (SIS) -Teflon® -Thermoplastic Polyolefin (TPO) -Trespa® Meteon®\*\*\* - Ultra High Molecular Weight Polyethylene (UHMWPE) -Wood

\* A soft plastic cardboard made with super soft super flexible PVC. \*\* A polystyrene foam board bonded between two layers of Luxcell® wood-fiber veneer. \*\*\* Decorative high-pressure compact laminate (HPL) with an integral surface.

SPECIFICATIONS	
Manufacturer	Amana Tool
Diameter	16 in (400 mm)
Bore	1 in
Grind	MTC
Kerf	0.145

## SPECIFICATIONS

<b>Pinholes</b>	--
<b>Plate</b>	.118 in
<b>Teeth</b>	120
<b>Hook Angle</b>	2 deg negative hook