

Edge of Arlington Saw & Tool, Inc.

124 South Collins
 Arlington, TX 76010
 Phone: 817-461-7171 • Fax: 817-795-6651
 Toll Free: 888-461-7171
 Email: info@eoasaw.com
 Website: www.eoasaw.com



Item #LU3E02, Freud® Saw Blades to Cut Bilaminated Panels: LU3E Series \$91.94


Thank you for shopping with us!

Freud is one of the few manufacturers of woodworking tools in the world that produces its own Micrograin Carbide for each tool application.


Silent Sawblade. Anti-vibration Design. Silver I.C.E. Coating prevents build-up on the blade surface and keeps the blade running cooler and cleaner.

Machines: Circular saws, horizontal and vertical panel-sizing machines
 Features: Flat triple-chip tooth with negative cutting angle
 Material: Bilaminated panels

Ideal For: To size bilaminated panels without the employment of the scoring sawblade up to 40mm thick. In detail, it is suitable to work melamine-coated panels.




Tooth features - Caratteristiche del dente



Minimum and maximum RPM based on the blade diameter.
 Fascia dei R. giri minimo e massimo consigliati in funzione del diametro della lama.



Working with spindle over the working plane
 Lavorazione con albero sopra il piano di lavoro



	Ultimate Eccellente	High Ottimo	Good Buono
Wood composites Composti di legno		●	
Veneered Impialaccati	●		
Laminates Laminati	●		

To peruse more comprehensive information on Freud® Tools Industrial Circular Saws—correct saw blade use, informational tips, technical information—click on the link to [Industrial Saw Blades Catalog](#).

SPECIFICATIONS	
Manufacturer	Freud Tools

SPECIFICATIONS

Diameter	250 mm
Arbor	30 mm
Pinholes	2/7/42 + 2/9/46.4 + 2/10/60
Grind	TCG
Plate	2.2 mm
Kerf	3.2 mm
Teeth	60
Type	Sliding & Vertical Panel Sizing