


Edge of Arlington Saw & Tool, Inc.

124 South Collins
Arlington, TX 76010
Phone: 817-461-7171 • Fax: 817-795-6651
Toll Free: 888-461-7171
Email: info@eoasaw.com
Website: www.eoasaw.com



Item #LU84R009, Freud Combination Blades: LU84R \$89.75

Thank you for shopping with us!

In many woodworking shops, one saw must serve multiple purposes. It must rip a piece of 4/4 oak and also crosscut a sheet of 3/4" plywood. The groups of five teeth include one flat tooth for ripping, followed by four alternate top bevel teeth for crosscutting, and a large gullet for effective chip clearance. This blade also features laser-cut anti-vibration slots, practically eliminating the vibration that resonates in standard blades. With this ultimate combination blade, there is no need for stabilizers.

Premium TiCo™ HI-Density Carbide Combination Blend for Maximum Performance. Large Gullets in front of flat top rakers allow for fast ripping and easy chip removal. Laser-Cut Anti-Vibration Slots drastically reduce vibration and sideways movement in the cut, extending blade life and giving a crisp, splinter-free flawless finish.

Perma-Shield™ Non-Stick Coating reduces blade drag, protects the blade from corrosion and pitch buildup.

Ideal For: Crosscuts (3/4" to 3-1/2") & Rips (3/8" to 1-1/2").

Tip: Kickbacks are one of the most dangerous hazards in woodworking. Choose a saw blade with a kickback-reducing design. This design places a chip limiter before each tooth, restricting tooth bite to the maximum safe amount for a more secure work environment.

SPECIFICATIONS

Diameter	9 in
Arbor	5/8 in
Kerf	.126 in
Plate	.087 in
Teeth	40 COMB
Type	Perma-SHIELD
Manufacturer	Freud Tools