

## Edge of Arlington Saw & Tool, Inc.


124 South Collins  
Arlington, TX 76010  
Phone: 817-461-7171 • Fax: 817-795-6651  
Toll Free: 888-461-7171  
Email: [info@eoasaw.com](mailto:info@eoasaw.com)  
Website: [www.eoasaw.com](http://www.eoasaw.com)



TOOLS



CUTS



### Item #LU95R012, Freud Solid Surface Blades: LU95R Series

**\$157.53**

Thank you for shopping with us!

**Application: Heavy Duty Solid Surface Blades for Swirl & Burn-Free Cuts**

This blade features teeth with a specially designed triple chip grind for leaving swirl-free cuts in solid surface materials such as Dupont®, Corian®, Wilsonart Gibraltar®, and SSV Fountainhead®. The laser-cut anti-vibration slots reduce the sideways movement of the cutting edge against the solid surface material, dramatically extending cutting life. With this ultimate solid surface blade, there is no need for stabilizers.

Premium TiCo™ HI-Density Carbide Plastic Blend for Maximum Performance. Thin Kerf allows for faster feed rate and reduced waste. Laser-Cut Anti-Vibration Slots drastically reduce vibration and sideways movement in the cut, extending blade life and giving a crisp, splinter-free flawless finish. Silver Ice™ Coating resists corrosion and pitch build-up; Perma-Shield® Non-Stick Coating reduces blade drag, protects the blade from corrosion and pitch buildup.

Ideal For: Solid surface materials such as Dupont® Corian®, Wilsonart Gibraltar®, and SSV Fountainhead®. Depth of cut (1/4" to 1-5/8" ).

**Tip:** Proper blade height on a table saw is one half of the carbide tip higher than the material to cut

## SPECIFICATIONS

<b>Diameter</b>	12 in
<b>Arbor</b>	1 in
<b>Kerf</b>	.126 in
<b>Plate</b>	.087 in
<b>Teeth</b>	84 MTCG
<b>Type</b>	Perma-SHIELD
<b>Manufacturer</b>	Freud Tools