

## Edge of Arlington Saw & Tool, Inc.

124 South Collins  
Arlington, TX 76010  
Phone: 817-461-7171 • Fax: 817-795-6651  
Toll Free: 888-461-7171  
Email: [info@eoasaw.com](mailto:info@eoasaw.com)  
Website: [www.eoasaw.com](http://www.eoasaw.com)



TOOLS



CUTS



### Item #LU96R006M20, Freud Thin Kerf Double-Sided Laminate/Melamine Blade: LU96R Series \$63.75

Thank you for shopping with us!

#### Application: For Ultra Long Life in Double-Sided Man-made Materials

The LU96R is a thin kerf blade that is designed to give long life and excellent finish on the top and bottom of laminates, melamine, and veneered plywood. The laser-cut anti-vibration design yields the plate acoustically dead. This reduces the sideways movement of the cutting edge to prevent chipping in man-made materials such as laminates. This dramatically extends cutting life and finish. No scoring blades needed with this blade!

Premium TiCo™ HI-Density Carbide Laminate Blend for Maximum Performance. Triple Chip Grind (TCG) Tooth Design with a positive hook angle for long life in production applications. Thin Kerf requires less power and allows for faster feed rate. Perma-Shield® Non-Stick Coating reduces blade drag, protects the blade from corrosion and pitch buildup.

Ideal For: Double-sided laminates, melamine & veneered plywood. Depth of cut (1/4" min to 1-5/8" max).

**Tip:** Proper blade height is essential to chip-free cuts. If you experience chipping on the bottom of the material, lower the blade slightly. If there is chipping on the top of the material, the blade height should be increased slightly.

## SPECIFICATIONS

<b>Diameter</b>	160 mm
<b>Arbor</b>	20 mm
<b>Kerf</b>	.087 in
<b>Plate</b>	.063 in
<b>Teeth</b>	48 TCG
<b>Type</b>	Perma-SHIELD - Ideal for Track Saws

## SPECIFICATIONS

**Manufacturer**

Freud Tools