Edge of Arlington Saw & Tool, Inc.

124 South Collins Arlington, TX 76010 Phone:817-461-7171 • Fax: 817-795-6651 Toll Free: 888-461-7171 Email: info@eoasaw.com Website: www.eoasaw.com



Item #LU97R012, Freud Double Sided Laminate/Melamine Blade: LU97R \$149.56

Thank you for shopping with us!

Application: For Ultra Long Life in Double-Sided Man-made Materials

Designed to give long life and excellent finish on the top and bottom of laminates, melamine, and veneered plywood. The lasercut anti-vibration design yields the plate acoustically dead. This reduces the sideways movement of the cutting edge to prevent chipping in man-made materials, such as laminates. This dramatically extends cutting life and finish. No scoring blades needed with this blade!

Premium TiCo[™] HI-Density Carbide Laminate Blend for Maximum Performance. Triple Chip Grind (TCG) Tooth Design with a positive hook angle for long life in production applications. Laser-Cut Anti-Vibration Slots drastically reduce vibration and sideways movement in the cut, extending blade life and giving a crisp, splinter-free flawless finish. Silver Ice[™] Coating resists corrosion and pitch buildup; Perma-Shield[®] Non-Stick Coating reduces blade drag, protects the blade from corrosion and pitch buildup.

Ideal For: Excellent finish on the top and bottom of laminates, melamine & veneered plywood. Depth of cut (1/4" min to 1-5/8" max).

Tip: Proper blade height is essential to chip-free cuts. If you experience chipping on the bottom of the material, lower the blade slightly. If there is chipping on the top of the material, the blade height should be increased slightly.

SPECIFICATIONS	
Diameter	12 in
Arbor	1 in
Kerf	.126 in
Plate	.087 in
Teeth	96 TCG

SPECIFICATIONS	
Туре	Perma-SHIELD
Manufacturer	Freud Tools