Edge of Arlington Saw & Tool, Inc.

124 South Collins Arlington, TX 76010

Phone:817-461-7171 • Fax: 817-795-6651

Toll Free: 888-461-7171
Email: info@eoasaw.com
Website: www.eoasaw.com





Thank you for shopping with us!

Application: Long Life Production Blades for Single-Sided Laminates, Chipboard, and Other Man-made Materials

This fast-cutting blade is ideal for a perfect finish on one side of laminates and melamines. The Perma-SHIELD® coating makes these blades resistant to friction and heat buildup. Coated blades pull 1/3 less on the saw, which translates to 33% more cutting power. The 5° or 10° hook angle and a triple chip grind provide fast cuts and long cutting life.

Premium TiCo™ HI-Density Carbide Laminate Blend for Maximum Performance. Triple Chip Grind (TCG) Tooth Design with a positive hook angle for long life in production applications. Positive Hook Angle for fast cutting and easy feed. Perma-Shield® Non-Stick Coating reduces blade drag, protects the blade from corrosion and pitch buildup.

Ideal For: Single-Sided Laminates, Chipboard, and other Manmade Materials. Depth of cut (1/2" min to 2-3/4" max).

Tip: When cutting man-made products such as laminates, melamines, MDF, and particle board, use a blade with Triple Chip Grind (TCG) for longest blade life.

| SPECIFICATIONS | |
|----------------|--------------|
| Diameter | 7 in |
| Arbor | 5/8 in |
| Kerf | .126 in |
| Hook Angle | 5 deg |
| Plate | .087 in |
| Teeth | 56 TCG |
| Туре | Perma-SHIELD |
| Manufacturer | Freud Tools |