

## Edge of Arlington Saw & Tool, Inc.

124 South Collins  
 Arlington, TX 76010  
 Phone: 817-461-7171 • Fax: 817-795-6651  
 Toll Free: 888-461-7171  
 Email: [info@eoasaw.com](mailto:info@eoasaw.com)  
 Website: [www.eoasaw.com](http://www.eoasaw.com)



### Item #MD10-601R, Amana A.G.E. Series General Purpose Saw Blades: TCG Grind, AmorMax™ Coating \$73.39

















Thank you for shopping with us!


#### Designed for clean cuts in plywood and single-sided laminates.

These blades are specifically designed for clean cuts in plywood and single-sided laminates. The greater number of teeth, triple-chip grind, and 12° hook angle provide an excellent balance between feed resistance and finish. For a chip-free edge on both top and bottom sides of the double-sided laminates, it is recommended to use [a scoring blade](#) along with these blades.

MD10-601R: AmorMax™ non-stick coating.

**Warning:** Not recommended for cutting non-ferrous alloys and melamine.



	NOT RECOMMENDED	FAIR	GOOD	EXCELLENT
 CHIPBOARD				
 MDF				
 LAMINATE				
 CROSSCUT				
 PLYWOOD				
 RIPPING				
 NON-FERROUS ALLOYS				
 MELAMINE				



Soft / Hardwood Crosscut



Plastic Laminate, Single & Double Sided



## SPECIFICATIONS

<b>Manufacturer</b>	Amana Tool
<b>Diameter</b>	10 in
<b>Bore</b>	5/8 in
<b>Hook Angle</b>	12 deg
<b>Kerf</b>	0.126 in
<b>Note</b>	ArmorMax non-stick coating
<b>Pinholes</b>	--
<b>Plate</b>	0.087 in
<b>RPM</b>	7,600
<b>Teeth</b>	60