

## Edge of Arlington Saw & Tool, Inc.

124 South Collins  
Arlington, TX 76010  
Phone: 817-461-7171 • Fax: 817-795-6651  
Toll Free: 888-461-7171  
Email: [info@eoasaw.com](mailto:info@eoasaw.com)  
Website: [www.eoasaw.com](http://www.eoasaw.com)



















### Item #MD12-961-30, Amana A.G.E. Series General Purpose Saw Blades: TCG Grind \$107.63


Thank you for shopping with us!

#### Designed for clean cuts in plywood and single-sided laminates.

These blades are specifically designed for clean cuts in plywood and single-sided laminates. The greater number of teeth, triple-chip grind, and 12° hook angle provide an excellent balance between feed resistance and finish. For a chip-free edge on both top and bottom sides of the double-sided laminates, it is recommended to use a [scoring blade](#) along with these blades.

**Warning:** Not recommended for cutting non-ferrous alloys and melamine.



	NOT RECOMMENDED	FAIR	GOOD	EXCELLENT
 CHIPBOARD				
 MDF				
 LAMINATE				
 CROSSCUT				
 PLYWOOD				
 RIPPING				
 NON-FERROUS ALLOYS				
 MELAMINE				



Soft / Hardwood Crosscut



Plastic Laminate, Single & Double Sided



## SPECIFICATIONS

<b>Manufacturer</b>	Amana Tool
<b>Diameter</b>	300 mm
<b>Bore</b>	30 mm
<b>Hook Angle</b>	10 deg
<b>Kerf</b>	0.138 in
<b>Note</b>	--
<b>Pinholes</b>	30mm bore accepts: 2/10/60, 2/7/42, 2/9/46
<b>Plate</b>	0.098 in
<b>RPM</b>	6,200
<b>Teeth</b>	96