Edge of Arlington Saw & Tool, Inc.

124 South Collins Arlington, TX 76010

Phone:817-461-7171 • Fax: 817-795-6651

Toll Free: 888-461-7171
Email: info@eoasaw.com
Website: www.eoasaw.com




Item #RC-2242, Amana Tool Insert Carbide Spoilboard Surfacing, Rabbeting, Flycutter, Slab Leveler & Surface Planer 1 3/4" Dia x 15/32" (12mm) x 1/2" Shank Router Bit (Industrial) \$189.72

Thank you for shopping with us! Designed for planing & rabbeting the following materials: -MDF -Fiberboard -HDF/LDF -Balsa Core* -Epoxy (Epoxy Resins)* -High Density Urethane (HDU Board)* -Plastic/Acrylic* -Plywood/Chipboard* - Hardwood/Softwood* -Ultra-High-Molecular-Weight Polyethylene (UHMWPE)* *For optimal results and maximum insert life, replace inserts with optional general purpose knives #AMA-12 (sold separately). **Featuring:**

- 4-sided solid carbide insert knives
- Exclusive carbide grade for highest quality of cut
- · Maximum cutting efficiency
- Faster material removal process
- Longest tool life

These industrial router bits feature solid carbide insert knives with four cutting edges that allow users to flip the knife over when one side becomes dull, providing the highest-quality finish available on woodworking tools. Warning: Proper torques rating to tighten down screws is 2-3Nm Torques.



SPECIFICATIONS	
Manufacturer	Amana Tool
Cut Depth	1/2 in Max Cut Depth
Diameter	1 3/4 in
Cut Height, Length, or Width	12 mm
Knives	RCK-344
Overall Length	1 49/64 in
RPM	28,000
Shank	1/2 in
Replacement Parts	Screw #67115

SPECIFICATIONS	
Note	Best recommended by planing/flattening in surfaces of large solid wood slabs with a handheld router in router sleds. Features a 1/8 in radius 5 degree bevel, making this tool unique compared to other spoilboard bits. Not to be used for slot cutting. Warning: Proper Torques rating to tighten down screws is 2-3Nm Torques.