Edge of Arlington Saw & Tool, Inc.

124 South Collins Arlington, TX 76010 Phone:817-461-7171 • Fax: 817-795-6651 Toll Free: 888-461-7171 Email: info@eoasaw.com Website: www.eoasaw.com



Item #RC-2250, Amana Tool Insert Carbide Mini Spoilboard Surfacing, Rabbeting, Flycutter, Slab Leveler & Surface Planer 2+2 Flute Design 1-1/2" Dia x 1/2" x 1/2" Shank Router Bit (Industrial)

\$203.40

Thank you for shopping with us! Mini insert solid carbide spoilboard surfacing & rabbeting with scorer; great for cutting tight corners. Features unique 2+2 insert knife design that contains two cutting flutes and two up-shear scorers, which provide a smoother finish at the bottom of the cut than traditional two-knife style router bits. **TIP!: To produce MDF simulated shaker cabinet doors use RC-2250 or RC-2252. Square corners with** *#***45200 straight plunge router bit. Designed for planing & rabbeting the following materials:** • Balsa Core*

- Hardwood/Softwood*
- Chipboard*
- MDF
- Fiberboard
- HDF/LDF
- Plastic*

*For optimal results and maximum insert life, replace inserts with optional general purpose knives (sold separately). Warning: Proper torques rating to tighten down screws is 2-3Nm Torques. Optional General Purpose Knives: #AMA-12 & RCK-70. Replacement screws: bottom-(2) #67155, key #5015; sides-(2) #67115, key #5005. Max cutting depth: 1/4. THIS TOOL IS NOT DESIGNED TO PLUNGE! You must ramp down to a depth of 1/4 in deep over a 20 in run. Use the max RPM allowed (24,000) and start the feed rate at about 320 in per minute, and go up until you get waves, then back down to a smooth cut/finish. **Featuring:**

- 2+2 mini design for tighter corners
- 4-sided solid carbide insert knives
- Exclusive carbide grade for highest quality of cut
- Maximum cutting efficiency
- Faster material removal process
- Longest tool life

Torx key #5005 included These industrial router bits feature solid carbide insert knives with four cutting edges that allow users to flip the knife over when one side becomes dull, providing the highest-quality finish available on woodworking tools.



SPECIFICATIONS	
Manufacturer	Amana Tool
Diameter	1 1/2 in
Cut Height, Length, or Width	1/2 in
Knives	HMA-12, HCK-70. Optional GP: AMA-12 & RCK-70. Optional Solid Wood DLC Coated: AMA-12-DLC & RCK-70-DLC.
Overall Length	2 5/16 in
RPM	24,000
Туре	With scorer & 2+2 insert knife design
Replacement Parts	Screws: bottom-(2) #67155, key #5015; sides-(2) #67115, key #5005.
Note	