## Edge of Arlington Saw & Tool, Inc.

124 South Collins Arlington, TX 76010

Phone:817-461-7171 • Fax: 817-795-6651

Toll Free: 888-461-7171 Email: <u>info@eoasaw.com</u> Website: www.eoasaw.com



## Item #RC-2252, Amana Tool CNC Insert Carbide Spoilboard Surfacing, Rabbeting, Flycutter, Slab Leveler & Surface Planer 2+2 Flute Design 3-5/32" (80mm) Dia x 15/32" x 3/4" Shank Router Bit (Industrial) \$291.96

Thank you for shopping with us! CNC use only. Insert spoilboard, planing, and rabbeting router bit features unique 2+2 insert knife design. Contains two cutting flutes and two up-shear scorers, which provide a smoother finish at the bottom of the cut than traditional two-knife style router bits. Excellent results in MDF, balsa core, hardwood, softwood, and all man-made materials. A great tool for fast removal of materials over a large surface area. The scorer leaves an improved finish at the bottom of the cut. Utilizes 4-sided carbide inserts. TIP!: To produce MDF simulated shaker cabinet doors use RC-2250 or RC-2252. Square corners with #45200 straight plunge router bit. Designed for planing & rabbeting the following materials:

- Balsa Core\*
- Hardwood/Softwood\*
- Chipboard/Plywood\*
- MDF
- Plastic\*
- Fiberboard
- HDF/LDF

\*For optimal results and maximum insert life, replace inserts with optional general purpose knives; sold separately. **Featuring:** 

- 2+2 design
- 4-sided solid carbide insert knives
- Exclusive carbide grade for highest quality of cut
- · Maximum cutting efficiency
- Faster material removal process
- · Longest tool life

**Torx key #5005 included** These industrial router bits feature solid carbide insert knives with four cutting edges that allow users to flip the knife over when one side becomes dull, providing the highest-quality finish available on woodworking tools. Recommendations: For surfacing solid woods it is recommended to remove both bottom scorers. Warning: Proper torques rating to tighten down screws is 2-3Nm Torques.



outer bit.

with #45200 straight plunge



SPECIFICATIONS	
Manufacturer	Amana Tool
Diameter	3 5/32 in
Cut Height, Length, or Width	15/32 in
Knives	HMA-12, HCK-70. Optional General Purpose knives: AMA-12 & RCK-70. Optional solid wood: AMA-12-DLC & RCK-70-DLC

SPECIFICATIONS	
Note	CNC use only and not for use in router sled.
Replacement Parts	Screws: bottom (2) #67155; sides (2) 67110. Torx key: bottom #5015; sides (2) 5005
Overall Length	3 1/2 in
Shank	3/4 in
Туре	