

## Edge of Arlington Saw & Tool, Inc.

124 South Collins  
Arlington, TX 76010  
Phone:817-461-7171 • Fax: 817-795-6651  
Toll Free: 888-461-7171  
Email: [info@eoasaw.com](mailto:info@eoasaw.com)  
Website: [www.eoasaw.com](http://www.eoasaw.com)



### Item #RS-25540-U, Tenryu Rapid Cut Series Multi-Purpose Saw Blades

**\$91.80**

Thank you for shopping with us!

Tenryu's Premium Heavy Duty, Industrial, Multi-Purpose Blades.

Tenryu offers an entire line of industrial duty "work horse" blades that cover the 10" to 16" diameter range. These blades are all meant to be used on shop tools such as table saws. In addition, many models can be used on more specialized machinery with arbor hole adjustments. Each blade has a large carbide tip following the European tradition.

Value is key here. These blades are priced very competitively. Both the small shop and the corporate giant will appreciate quality industrial blades at attractive prices.

Each Blade Features:

- Individually hand-hammered, fully heat-hardened steel plates for flat, true, wobble-free operation.
- Aggressive grind angles for easy performance in heavy duty jobs. Honing carried out at 400 grit to limit microchipping and to produce a very keen edge.
- Large high-grade carbide tips selected for long life in woodworking applications.
- Ample side clearance provides for air flow between carbide and the workpiece, limits the likelihood of burning even on heavy rips. This also prevents premature dulling.

## SPECIFICATIONS

|                     |                                                         |
|---------------------|---------------------------------------------------------|
| <b>Manufacturer</b> | Tenryu                                                  |
| <b>Application</b>  | Ultra-thin kerf (.079) combination blade for table saws |
| <b>Diameter</b>     | 10 in                                                   |
| <b>Arbor</b>        | 5/8 in                                                  |
| <b>Grind</b>        | ATAF                                                    |
| <b>Kerf</b>         | 0.079                                                   |
| <b>Rake</b>         | 20                                                      |
| <b>RPM</b>          | 5,870                                                   |
| <b>Teeth</b>        | 40                                                      |