Edge of Arlington Saw & Tool, Inc.

124 South Collins Arlington, TX 76010

Phone:817-461-7171 • Fax: 817-795-6651

Toll Free: 888-461-7171
Email: info@eoasaw.com
Website: www.eoasaw.com



Item #TCK1640T25A, Everlast Truss & Component Saw - 16" Dia 40-Tooth 1.26" Bore 0.150" Plate 0.190" Kerf \$320.88

Thank you for shopping with us!

These saws are the workhorses of truss plants and are designed to provide a long service life and excellent cutting performance. Countersunk (80°) holes will accept 5/16" flat head bolt.

Alternate Top Bevel - ATB - Each tooth has top bevel typically between 10 and 20 degrees. Two teeth are required to provide a full kerf cut. Provides low cutting pressures, which reduce material tearing during the cutting process and provides a fine cutting finish. Best performance cross cutting.

SPECIFICATIONS	
Manufacturer	Everlast
Bore	1.26 in
Diameter	16 in
Countersink	2.25" ; 2.265" Bolt Hole Circle Dia
Kerf	0.190 in - 4.8 mm
Machine	Koskovich
Grind	АТВ
Plate	0.150 in - 3.8 mm
Teeth	40
Hole Size	2.25 in; 2.265 in Bolt Hole Circle Dia