

Edge of Arlington Saw & Tool, Inc.

124 South Collins
Arlington, TX 76010
Phone: 817-461-7171 • Fax: 817-795-6651
Toll Free: 888-461-7171
Email: info@eoasaw.com
Website: www.eoasaw.com



**Item #TR1080A, Everlast 10" Dia 80-Tooth
5/8" Bore .087" Plate 0.056" Thin Rim
Plate 0.087" Kerf Thin Rim Saw - Alternate
Top Bevel
\$298.41**

Thank you for shopping with us!

The perfect saw to use where there is a need for a minimum of stock removal per cut, as in the cutting of plastic or veneer strips for edge banding. Maximum depth of cut on Thin Rim blade is 1-3/4 inches. Alternate design with thin saw plate and thick support hubs on both sides is available.

Alternate Top Bevel - ATB - Each tooth has top bevel typically between 10 and 20 degrees. Two teeth are required to provide a full kerf cut. Provides low cutting pressures, which reduce material tearing during the cutting process and provides a fine cutting finish. Best performance crosscutting.

SPECIFICATIONS

Manufacturer	Everlast
Bore	5/8 in
Diameter	10 in
Grind	ATB
Kerf	0.087 in
Plate	Plate Thickness 0.087"/2.2mm Thin Rim Plate Thickness 0.056"/1.4mm
Teeth	80
Hook Angle	5 deg