

Edge of Arlington Saw & Tool, Inc.

124 South Collins
Arlington, TX 76010
Phone: 817-461-7171 • Fax: 817-795-6651
Toll Free: 888-461-7171
Email: info@eoasaw.com
Website: www.eoasaw.com



Item #TR1210A, Everlast 12" Dia 100-Tooth 1" Bore .095" Plate 0.062" Thin Rim Plate 0.091" Kerf Thin Rim Saw - Alternate Top Bevel

\$337.78

Thank you for shopping with us!

The perfect saw to use where there is a need for a minimum of stock removal per cut, as in the cutting of plastic or veneer strips for edge banding. Maximum depth of cut on Thin Rim blade is 1-3/4 inches. Alternate design with thin saw plate and thick support hubs on both sides is available.

Alternate Top Bevel - ATB - Each tooth has top bevel typically between 10 and 20 degrees. Two teeth are required to provide a full kerf cut. Provides low cutting pressures, which reduce material tearing during the cutting process and provides a fine cutting finish. Best performance crosscutting.

SPECIFICATIONS

Manufacturer Everlast

Bore 1 in

Diameter 12 in

Grind ATB

Kerf 0.091 in

Plate Plate Thickness 0.095 in/2.4mm Thin Rim Plate Thickness 0.062 in/1.6mm

Teeth 100

Hook Angle 5 deg